



Bits mit 1/4" Sechskantantrieb DIN 3126 / ISO 1173 – C 6,3




Vielzahn XZN – zähhart

Modell	Best.-Nr.	SW #	L mm	Ø mm	VE
XZN4-C6.3-25	116010	4	25	4	10
XZN5-C6.3-25	116011	5	25	5	10
XZN6-C6.3-25	116012	6	25	6	10
XZN8-C6.3-25	116013	8	25	8	10
XZN10-C6.3-25	116014	10	25	10	10




Innenvierkant – zähhart

Modell	Best.-Nr.	SW #	L mm	Ø mm	VE
SQ0-C6.3-25	116510	0	25	–	10
SQ1-C6.3-25	116511	1	25	–	10
SQ2-C6.3-25	116512	2	25	–	10
SQ3-C6.3-25	116513	3	25	–	10
SQ4-C6.3-25	116514	4	25	–	10



Innenvierkant – CR

Modell	Best.-Nr.	SW #	L mm	Ø mm	VE
SQ0-C6.3-25-CR	116570	0	25	–	10
SQ1-C6.3-25-CR	116571	1	25	–	10
SQ2-C6.3-25-CR	116572	2	25	–	10
SQ3-C6.3-25-CR	116573	3	25	–	10




Torq-Set® – zähhart

Modell	Best.-Nr.	SW #	L mm	Ø mm	VE
TS0-C6.3-25	116600	0	25	–	10
TS1-C6.3-25	116601	1	25	–	10
TS2-C6.3-25	116602	2	25	–	10
TS3-C6.3-25	116603	3	25	–	10
TS4-C6.3-25	116604	4	25	–	10
TS5-C6.3-25	116605	5	25	–	10
TS6-C6.3-25	116610	6	25	–	10
TS8-C6.3-25	116611	8	25	–	10
TS10-C6.3-25	116612	10	25	–	10
TS1/4-C6.3-25	116613	1/4	25	–	10



Tri-Wing® – zähhart

Modell	Best.-Nr.	SW #	L mm	Ø mm	VE
TW0-C6.3-25	116410	0	25	–	10
TW1-C6.3-25	116411	1	25	–	10
TW2-C6.3-25	116412	2	25	–	10
TW3-C6.3-25	116413	3	25	–	10
TW4-C6.3-25	116414	4	25	–	10
TW5-C6.3-25	116415	5	25	–	10
TW6-C6.3-32	116416	6	32	–	10
TW7-C6.3-32	116417	7	32	–	10
TW8-C6.3-32	116418	8	32	–	10



Spanner

Modell	Best.-Nr.	Größe #	L mm	Ø mm	VE
SP4-C6.3-25	116710	4	25	4,5	10
SP6-C6.3-25	116712	6	25	5,5	10
SP8-C6.3-25	116713	8	25	5,5	10
SP10-C6.3-25	116714	10	25	6,5	10



Weitere Infos auf unserer Website.

24/7

* In Verbindung mit Universal-Bithalter oder für direkten Maschinenanschluss, vgl. Tabelle „Zuordnung von Werkzeugantrieb und Maschine“ S. 72.

E-Mail: info@zemo-tools.de • Tel.: +49 (0)40 303 989 100 • Web: www.zemo-tools.de

ZEMO
www.zemo-tools.de