



# Verbindungssteile mit Vierkantantrieb nach DIN 3121 G



## Kugelgelenk\* – mit Stiftloch

Modell	Best.-Nr.	4kt Zoll	L mm	D1 mm	D2 mm	T mm	VE
KG1/4	313450	1/4	43	–	16	–	–
KG3/8	313451	3/8	50	–	24	–	–
KG1/2	313452	1/2	60	–	32	–	–
KG3/4	313458	3/4	90	–	44	–	–
KG3/4-L	313453	3/4	105	–	44	–	–
KG1	313455	1	110	–	54	–	–
KG1.1/2	313456	1 1/2	182	–	86	–	–

Ring+Stift nicht enthalten, bitte ggf. separat bestellen.



## Kugelgelenk\* – mit Kugelsicherung

Modell	Best.-Nr.	4kt Zoll	L mm	D1 mm	D2 mm	T mm	VE
KG1/4-KS	313410	1/4	43	–	16	–	–
KG3/8-KS	313411	3/8	50	–	24	–	–
KG1/2-KS	313412	1/2	60	–	32	–	–
KG3/4-KS	313413	3/4	90	–	44	–	–





## Kugelgelenk\* – mit Federstift

Modell	Best.-Nr.	4kt Zoll	L mm	D1 mm	D2 mm	T mm	VE
KG1/4-FS	313350	1/4	45	18	13	–	–
KG3/8-FS	313351	3/8	60	25	22	–	–
KG1/2-FS	313353	1/2	68	31	25	–	–
KG1/2-FS	313355	1/2	150	30	25	–	–



## Gummiring & Sicherungsstift

Modell	Best.-Nr.	Größe Zoll	–	D1 mm	D2 mm	–	VE
RS-1/4	210950	1/4	–	–	13	–	5
RS-3/8	222050	3/8	–	–	13	–	5
RS-1/2	240510	1/2	–	–	–	–	5
RS-3/4	250810	3/4	–	–	–	–	5
RS-1	260850	1"	–	–	54	–	5
RS-1.1/2	270210	1 1/2	–	–	–	–	5
RS-2.1/2	280050	2 1/2	–	–	–	–	5



Weitere Infos auf unserer Website.

24/7

\* von der Herstellergarantie ausgenommen.

E-Mail: info@zemo-tools.de • Tel.: +49 (0)40 303 989 100 • Web: www.zemo-tools.de

**ZEMO**  
www.zemo-tools.de