




Innensechskant Inbus® – normal

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L1 mm	VE
K1/4-A2.5	210730	2,5	35	–	13	4,0	5
K1/4-A3	210731	3	35	–	13	6,0	5
K1/4-A4	210732	4	35	–	13	6,0	5
K1/4-A5	210733	5	35	–	13	6,0	5
K1/4-A6	210734	6	35	–	13	8,0	5
K1/4-A7	210735	7	35	–	13	8,0	5
K1/4-A8	210736	8	35	–	13	8,0	5
K1/4-A9	210737	9	35	–	13	10	5
K1/4-A10	210738	10	35	–	13	10	5




Gummiring & Sicherungsstift

Modell	Best.-Nr.	Größe Zoll	–	D1 mm	D2 mm	–	VE
RS-1/4	210950	1/4	–	–	13	–	5



Innensechsrund Torx® TX – normal

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
K1/4-T5	210850	T5	35	–	13	2,0	5
K1/4-T6	210851	T6	35	–	13	2,0	5
K1/4-T7	210852	T7	35	–	13	2,0	5
K1/4-T8	210853	T8	35	–	13	2,0	5
K1/4-T9	210854	T9	35	–	13	2,0	5
K1/4-T10	210855	T10	35	–	13	2,8	5
K1/4-T15	210856	T15	35	–	13	2,8	5
K1/4-T20	210857	T20	35	–	13	2,8	5
K1/4-T25	210858	T25	35	–	13	3,0	5
K1/4-T27	210859	T27	35	–	13	3,0	5
K1/4-T30	210860	T30	35	–	13	3,8	5



Innensechsrund Torx® TR – Tamper Resistant

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
K1/4-TR8	210913	TR 8	35	–	13	2,0	5
K1/4-TR9	210914	TR 9	35	–	13	2,0	5
K1/4-TR10	210915	TR 10	35	–	13	2,8	5
K1/4-TR15	210916	TR 15	35	–	13	2,8	5
K1/4-TR20	210917	TR 20	35	–	13	2,8	5
K1/4-TR25	210918	TR 25	35	–	13	3,0	5
K1/4-TR27	210919	TR 27	35	–	13	3,0	5
K1/4-TR30	210920	TR 30	35	–	13	3,8	5

