




Innensechskant Inbus® – normal

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L1 mm	VE
K3/8-A3	221310	3	50	–	19	16	5
K3/8-A4	221311	4	50	–	19	16	5
K3/8-A5	221312	5	50	–	19	16	5
K3/8-A6	221313	6	50	–	19	16	5
K3/8-A7	221314	7	50	–	19	16	5
K3/8-A8	221315	8	50	–	19	16	5
K3/8-A9	221316	9	50	–	19	16	5
K3/8-A10	221317	10	50	–	19	16	5
K3/8-A11	221318	11	50	–	19	16	5
K3/8-A12	221319	12	50	–	19	16	5
K3/8-A13	221320	13	50	–	19	16	5
K3/8-A14	221321	14	50	–	19	16	5
K3/8-A15	221322	15	50	–	19	16	5
K3/8-A16	221323	16	50	–	19	16	5



Innensechskant Inbus® – tief

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L1 mm	VE
K3/8-A3L	221330	3	150	–	19	16	5
K3/8-A4L	221331	4	150	–	19	16	5
K3/8-A5L	221332	5	150	–	19	16	5
K3/8-A6L	221333	6	150	–	19	16	5
K3/8-A7L	221334	7	150	–	19	16	5
K3/8-A8L	221335	8	150	–	19	16	5
K3/8-A9L	221336	9	150	–	19	16	5
K3/8-A10L	221337	10	150	–	19	16	5
K3/8-A11L	221338	11	150	–	19	16	5
K3/8-A12L	221339	12	150	–	19	16	5
K3/8-A13L	221340	13	150	–	19	16	5
K3/8-A14L	221341	14	150	–	19	16	5
K3/8-A15L	221342	15	150	–	19	16	5
K3/8-A16L	221343	16	150	–	19	16	5



Innensechskant Inbus® – mit Gelenk*

Modell	Best.-Nr.	SW mm	L mm	D1 mm	D2 mm	L1 mm	VE
KG3/8-A5	221350	5	60	–	24	11	5
KG3/8-A6	221351	6	60	–	24	11	5
KG3/8-A7	221352	7	60	–	24	15	5
KG3/8-A8	221353	8	60	–	24	15	5
KG3/8-A9	221354	9	60	–	24	15	5
KG3/8-A10	221355	10	60	–	24	15	5
KG3/8-A11	221356	11	60	–	24	15	5
KG3/8-A12	221357	12	60	–	24	15	5
KG3/8-A13	221358	13	60	–	24	15	5
KG3/8-A14	221359	14	60	–	24	15	5
KG3/8-A15	221360	15	60	–	24	15	5
KG3/8-A16	221361	16	60	–	24	15	5



Halter & auswechselbare Einsätze

Modell	Best.-Nr.	SW	L mm	D1 mm	D2 mm	T mm	VE
K3/8-AWE7/16	221410	7/16	32	22,0	22	–	–
AWE7/16-A5	221450	5	35	–	–	–	5
AWE7/16-A6	221451	6	35	–	–	–	5
AWE7/16-A8	221452	8	35	–	–	–	5
AWE7/16-A10	221453	10	35	–	–	–	5
AWE7/16-A12	221454	12	35	–	–	–	5
AWE7/16-A14	221455	14	35	–	–	–	5
AWE7/16-A17	221456	17	35	–	–	–	5



Innensechskeil RIBE® – normal

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
K3/8-R5	221830	R5	50	–	19	4,5	5
K3/8-R6	221831	R6	50	–	19	5,0	5
K3/8-R7	221832	R7	50	–	19	6,5	5
K3/8-R8	221833	R8	50	–	19	7,5	5
K3/8-R10	221834	R10	50	–	19	9,0	5
K3/8-R12	221835	R12	50	–	19	10,0	5
K3/8-R14	221836	R14	50	–	19	12,0	5
K3/8-R16	221837	R16	50	–	19	14,0	5



Weitere Infos
auf unserer
Website.

24/7

* von der Herstellergarantie ausgenommen.



Innensechsrund Torx® TX – normal ¹⁾

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
K3/8-T9	221650	T9	50	–	19	2,8	5
K3/8-T10	221651	T10	50	–	19	2,8	5
K3/8-T15	221652	T15	50	–	19	2,8	5
K3/8-T20	221653	T20	50	–	19	3,0	5
K3/8-T25	221654	T25	50	–	19	3,0	5
K3/8-T27	221655	T27	50	–	19	3,8	5
K3/8-T30	221656	T30	50	–	19	3,8	5
K3/8-T40	221657	T40	50	–	19	4,3	5
K3/8-T45	221658	T45	50	–	19	5,0	5
K3/8-T47	221659	T47	50	–	19	5,0	5
K3/8-T50	221660	T50	50	–	19	5,5	5

¹⁾ Größe T20 bis T55 auch in Länge 150 mm lieferbar.



Innensechsrund Torx® TX – mit Gelenk*

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
KG3/8-T20	221710	T20	60	–	24	3,0	5
KG3/8-T25	221711	T25	60	–	24	3,0	5
KG3/8-T27	221712	T27	60	–	24	3,8	5
KG3/8-T30	221713	T30	60	–	24	3,8	5
KG3/8-T40	221714	T40	60	–	24	4,3	5
KG3/8-T45	221715	T45	60	–	24	5,0	5
KG3/8-T47	221716	T47	60	–	24	5,0	5
KG3/8-T50	221717	T50	60	–	24	5,5	5
KG3/8-T55	221718	T55	60	–	24	5,5	5



Innensechsrund Torx® TR – Tamper Resistant

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
K3/8-TR20	221750	TR20	50	–	19	3,0	5
K3/8-TR25	221751	TR25	50	–	19	3,0	5
K3/8-TR27	221752	TR27	50	–	19	3,8	5
K3/8-TR30	221753	TR30	50	–	19	3,8	5
K3/8-TR40	221754	TR40	50	–	19	4,3	5
K3/8-TR45	221755	TR45	50	–	19	5,0	5
K3/8-TR47	221756	TR47	50	–	19	5,0	5
K3/8-TR50	221757	TR50	50	–	19	5,5	5
K3/8-TR55	221758	TR55	50	–	19	5,5	5



Innenvielzahn XZN – normal

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
K3/8-XZN5	221810	M5	50	–	19	7,0	5
K3/8-XZN6	221811	M6	50	–	19	7,0	5
K3/8-XZN8	221812	M8	50	–	19	9,0	5
K3/8-XZN10	221813	M10	50	–	19	9,0	5
K3/8-XZN12	221814	M12	50	–	19	11,0	5
K3/8-XZN14	221815	M14	50	–	19	11,0	5
K3/8-XZN16	221816	M16	50	–	19	13,0	5




Innenvielzahn XZN – tief

Modell	Best.-Nr.	SW #	L mm	D1 mm	D2 mm	L1 mm	VE
K3/8-XZN5-L	221850	M5	100	–	19	7,0	5
K3/8-XZN6-L	221851	M6	100	–	19	7,0	5
K3/8-XZN8-L	221852	M8	100	–	19	9,0	5
K3/8-XZN10-L	221853	M10	100	–	19	9,0	5
K3/8-XZN12-L	221854	M12	100	–	19	11,0	5
K3/8-XZN14-L	221855	M14	100	–	19	11,0	5
K3/8-XZN16-L	221856	M16	100	–	19	13,0	5
K3/8-XZN5-120	221870	M5	120	–	19	7,0	5
K3/8-XZN6-120	221871	M6	120	–	19	7,0	5
K3/8-XZN8-120	221872	M8	120	–	19	9,0	5
K3/8-XZN10-120	221873	M10	120	–	19	9,0	5
K3/8-XZN12-120	221874	M12	120	–	19	11,0	5
K3/8-XZN14-120	221875	M14	120	–	19	11,0	5
K3/8-XZN16-120	221876	M16	120	–	19	13,0	5



Gummiring & Sicherungsstift

Modell	Best.-Nr.	Größe Zoll	–	D1 mm	D2 mm	–	VE
RS-3/8	222050	3/8	–	–	13	–	5



* von der Herstellergarantie ausgenommen.

Weitere Infos
auf unserer
Website.



24/7